



^{1.} Dušan GRUDEN

QUESTION THAT IS ASKED FOR DECADES: WHO WILL MOVE OUR CARS IN THE FUTURE?

^{1.} Ditzingen, GERMANY

Abstract: For decades, discussions on road traffic have been followed by forecasts on limited reserves of mineral oil and other fossil fuels, by increased demands regarding the vehicle's economy and by more and more severe legislations regarding reduction of CO₂ emission and noxious components in exhaust gases. The question of which power units will drive the automobiles of the future or which will replace the internal combustion piston engine in the next 10 to 15 years, has not lost its actuality even after 130 years of engine development. Energy supply has the key role in answering this question. Forecasts that the known reserves of mineral oil will be spent in the next 30 to 40 years and that the four-stroke piston engine will be replaced by better power units have been repeated for several decades.

Keywords: car, road traffic, exhaust gases, energy supply

HISTORY - A VIEW AT THE PAST

For many decades the question has been set on which power units will drive the automobiles of future, that is who will replace the piston internal combustion engine (IC engine) in the next 10 to 15 years? This question has not lost its actuality even today and the generation of engineers and scientists currently engaged in these problems has an impression that development had never been as dynamic and diverse as nowadays.

The French writer, André Malraux, had said: "If you want to read the future, then you should scroll through the past!"

For almost 140 years, the piston IC engine has been without the competition as a power unit, not only for motor vehicles - automobiles, but in many other areas of human activities. During historical development, many other power units (Figure 1) have been investigated, none of which, with a sum of its features, had succeeded to establish itself in any field of application of the IC engines [1].

For several decades, discussions on road traffic have been followed by forecasts on limited reserves of mineral oil and other fossil fuels, by increased demands regarding the vehicle's economy and by more and more severe legal regulations regarding reduction of noxious exhaust emission and carbon dioxide (CO₂) emission.

Neuspele alternative:
Gasna turbina, Stirling Motor, Parni motor, Wankel Motor




Figure 1: Unsuccessful alternatives

THE STATE OF THE ART

From year to year, the modern vehicles are safer, more reliable and their negative impact on environment is getting smaller. In spite of this, emission and fuel consumption must be further reduced so their impact on human environment would be as small as possible

It is very interesting that, despite huge efforts to replace the conventional piston engine with some other, better power unit, and despite the forecasts that it could not fulfil more and more severe legislation set in front of the automobile, it has shown a very great development potential that has enabled it to fulfil all demands set before it so far.

Pretty picture of the achieved engine progress is painted by Porsche 911 vehicle which has been evolutionary and continually developing for 45 years. At the first test of exhaust emission performed in 1966, a former Porsche 911 vehicle with the engine displacement of $V_H = 2.0 \text{ dm}^3$ and the power output of 130 HP (96 kW), has had fuel consumption of 15.4 l per 100 km. The modern Porsche 911 vehicle has engine displacement of 3.6 dm^3 and the power output of 295 kW (400 HP) and the fuel consumption (at the same test) amounts to 8,2 l per 100 km, that is, it is 47% lower than its predecessor.

Of course, the toxic components from the exhaust emission in modern engines are incomparably lower than in their predecessors. The same amount of legally limited components (CO, HC, NO_x) emitted by a single automobile half a century ago is being emitted by 300 to 500 modern automobiles.

ECOLOGICAL DEMANDS SET BEFORE THE MOTOR VEHICLE

After the distance travelled for almost 140 years, IC engine, in its further development, must take more into account the social framework in which it is placed. The central place thereby belongs to:

- increasing anthropogenic emissions, in context with discussions on climate change,
- demographic changes in the world, with increasing number of population on Earth, who desire appropriate living conditions and with moving the age limits,
- increasing urbanization and
- limited reserves of fossil fuels that follow this development.

These social frameworks, as well as forecasts that both passenger and freight traffic will further grow in the next 20 years, explain the reason for more severe legislation set before the automobile and its power unit.

Firstly, there is reduction of energy consumption and closely related reduction of CO_2 emissions. Member countries of the European Union have adopted the so-called "20-20-20" program in 2007 or the program with the goal to reduce, between 2007 and 2020, energy consumption by 20%, to reduce CO_2 emission by 20% and to cover 20% of energy needs with so-called green energy, i.e. energy from the renewable sources.

Satisfaction of the legislation on reducing CO_2 emissions is one of the greatest challenges in development of new propulsion systems for vehicles. The European Union and Japan lead today in regard to the legislations on the reduction of CO_2 emissions; China prepares stricter regulations, followed by the USA and the other countries (Figure 2).




Figure 2: CO_2 emission reduction goals

According to current plan, the new passenger cars in the European Union will be allowed to emit, on average, just $95 \text{ gCO}_2/\text{km}$ (equivalent to $\approx 3.8 \text{ l}/100\text{km}$) from 2020 and this value should be reduced to $70 \text{ gCO}_2/\text{km}$ ($\approx 2.8 \text{ l}/100 \text{ km}$) from 2025. Currently, average value of CO_2 emission from passenger vehicles in Germany amounts to $148 \text{ gCO}_2/\text{km}$ (equivalent to $\approx 5.9 \text{ l}/100 \text{ km}$).

Of course, it is required that the automotive industry will continue to meet the ever harsher legislation on reduction of toxic components in the exhaust gases: carbon monoxide (CO), unburned hydrocarbons (HC), nitrogen oxides (NO_x) and particulate matter (PM). In the European Union, the strongest legal regulations for now, known as Euro 6, are predicted for the year 2014, while in the United States, with legal regulation LEV 2 (Low Emission Vehicles), the California Air Resources Board (CARB) has introduced the world's sharpest legal rules defined as SULEV (Super Ultra Low Emission Vehicles) $\text{CO} = 1,0 \text{ g}/\text{mi}$, $\text{NMHC} = 0,01 \text{ g}/\text{mi}$, $\text{NO}_x = 0,02 \text{ g}/\text{mi}$, $\text{PM} = 0,01 \text{ g}/\text{mi}$.

In order to classify the vehicle as PZEV (Partial Zero Emission Vehicle), the limit value recommended for SULEV vehicles must be guaranteed for 15 years of the vehicle operation and for the path of 120,000 miles (192.000 km) travelled. Evaporative emission of the stationary vehicle must be zero and the vehicle emissions at operating vehicle are controlled by OBD II (On Board Diagnostic II) system.

At the end of their "life" (End of Live Vehicles, ELV), passenger vehicles must meet the legal requirements on recycling, which in the European Union say that, from 2015, only 5% of vehicle weight may go to landfills, while 95% of vehicle weight must be used, either as material or energy.

TOPICS IN MODERN DEVELOPMENT OF IC ENGINES

IC engine is the most important engine of our mobile society. Its power output, reliability and fuel economy has not yet been achieved by any other alternative drive system – nor its current environmental friendliness.

To respond to the demands that are set upon it, the IC engine is still continuously and evolutionary developing. Its future depends, above all, on the further increase of efficiency in all areas of work. Former studies show that there is still considerable potential for further reductions in fuel consumption and CO₂ emissions that is estimated as at least 15% for both gasoline and Diesel engines in the short-term.

Downsizing

Under pressure from legislation, the main priority in the development of the engine is to reduce the fuel consumption. One of the attractive ways that is being increasingly used is the so-called "downsizing" or reducing the engine displacement, and thus the number of cylinders, while maintaining the desired power with the help of engine boosting. The fact that it is more important what cylinders do and not how many of them there are in the engine is slowly being accepted by the professional world.

"Downsizing" process, i.e. a supercharged engine with a relatively small displacement, had allowed the mass use of diesel engines in passenger vehicles 20 years ago and completely had thrown out the naturally aspirated diesel engines from applications, even in the field of commercial vehicles. While this process in diesel engines have long been the standard, manufacturers of vehicles with gasoline engines introduce in their programs more engines with reduced displacement and boosting (Fig.3), (Table 1) in order to meet CO₂ emission value of 130 gCO₂/km (equivalent to ≈ 5.2 l/100 km) required by the European Commission.




Figure 3: Trend of „downsized” gasoline engines in the world market

For the current generation of "downsized" turbocharged engines, the displacement is reduced by about 75% compared with the displacement of the naturally aspirated engine having the same power.

Table 1. The producers of turbocharged „downsized” engines

Producer	Displacement V _H [dm ³]	Number of cylinders	Power [kW]	CO ₂ [g/km]
Ford	1.0	3	100	
Kia		3		85
Fiat	0.875	2		
Nissan	1.2	3		95
Renault	0.9	3	66	
VW	0.8	2	35	

While complex charging systems with two (mostly turbo) compressors and direct injection at diesel engines have become almost standard, they begin to be more and more applied in gasoline engines, more often combined with variable valve timing scheme.

Working process

Success of internal combustion engines decisively depends on the combustion process, which takes place in the cylinder. Efforts to reduce the losses during charge exchange have led to the development of valve drives with variable valve timing.

Direct fuel injection with pressures of over 2000 bars has become a standard for diesel engines, while direct fuel injection with pressures of over 100 bars is more and more applied in gasoline engines as well. Gasoline engines with two injection systems increasingly appear on the market (Figure 4).

The first system allows the injection of the main fuel quantity in the initial stage of realization of the mixture. It is used to achieve homogeneous, lean mixture of fuel and air. The second, smaller

cooling, is required. Significant potential for reduction of mechanical losses is also in variable drive of auxiliary units on the vehicle: oil pump and water pump, which are involved in the work according to engine needs. Neglecting these potentials will not allow further necessary development of IC engines.

Modular design of engine

Of course, all these necessary measures to improve the engine, in addition to large investments in research and development, have resulted in the increase of production costs, including the price of the engine.

At the end of 1960-ies, before the introduction of legislation on reduction of exhaust emissions and fuel consumption, the production cost of one full 8-cylinder engine with the exhaust system in the U.S. was around 160 to 180 US \$. The production cost of modern engines that meet all legal requirements, are several times higher.

Despite the steady increase in production costs, continuous efforts are being made to reduce, as far as possible, this costs. Similarly, as many years ago, when the principle of "common platform" has been introduced in the construction of vehicle in order to reduce production costs, the modular design principle is also observed in the construction of the engine which represents a common base to build a family of engines with different displacements and numbers of cylinders by one producer.

Modules - joint groups and sets - are divided into groups of the base engine (piston mechanism, cylinder head, valve mechanism) and sets that are built on the engine (elements for filtering of the exhaust emission, intake system with integrated cooler for cooling the air for turbocharging).

Even in the engine concept phase, it is taken into account to modularize the engine to the greatest extent. In addition to reducing the production cost of the engine, modular construction offers possibility to produce the engines in different places and for different markets and applications. With no major losses in time, the engines can be built according to the different requirements that are set in the world in the standardized production plants, with always optimal technical solutions.

HYBRID DRIVE

In the last ten years, the vehicle power plants with two units: IC engine and electric motor have been recognized as the only alternative to a purely engine power unit that is produced in series

Micro hybrid

The initial step in this direction, the so-called "micro hybrid" or start-stop automatics (start-stop generator) has become an integral part of modern engines. In the city driving, fuel savings with this system amount to about 3% to 5%.

Mild hybrid

A "Mild Hybrid", in addition to the start-stop generators, uses power of the electric motor at start-up and acceleration of the vehicle. The energy needed for the electric motor is taken from a relatively small battery. Driving the vehicle for a long distance with electric motor is not possible for this system, because the battery is too small. Very often, braking energy recuperation is frequently used in this system during deceleration. Fuel savings during city driving and during new European driving cycle (NEUDC, New European Urban Driving Cycle) are about 15% to 20%.

Full hybride vehicle

Unlike "mild hybrid" vehicles, "full hybrid vehicles" have a battery of sufficient size, so the electric motor can drive the vehicle on a relatively long distance. Electric motor power is between 20 kW and 60 kW. Fuel savings or CO₂ emission reduction in the new European test are between 20% and 50%.

The key features of full hybrid vehicles are: pure electric driving ability at a certain distance, the exclusion of both engines operation at idle speed and braking energy recuperation.

Range extender. Plug in hybrid

High production costs and the price of full hybrid vehicles and their relatively small radius with pure electric drive, and the fact that most of the vehicle distances during the day do not exceed 30 to 60 km, led to hybrid vehicles solution with so-called "range extender" or "plug-in" systems.

Electric battery and electric motor power are dimensioned at these vehicles in a way that enables pure electric driving for about 50 to 60 km, for example, going to work and returning home, where the battery is charged during the night to ride the

next day. If the vehicle has to take more distance or the energy consumption is increased (lights, wipers, heating, air-condition), then the additional IC engine is engaged in operation, which is so dimensioned that allows unobstructed started drive ("range extender").

"Range extender" - IC engine, as modular part of a hybrid concept, provides compensation of known deficits of purely electric drive. To support the electric motor, one relatively small and light IC engine ($V_H = 0.3$ to 0.8 dm^3) with low production costs is used (Figure 7).




Figure 7: Investigated power units as „range extender”

Almost all alternative power units that were once offered to drive motor vehicles now are being investigated as possible variants for the position of the "range extender" engine (Wankel engine, two-stroke engine, gas turbine, etc.).

Despite all the efforts to promote the hybrid vehicles at the market as a serious alternative to a pure engine drive, their share in the total vehicle fleet is still very small: At the beginning of 2012, the number of new hybrid vehicles in traffic in Germany totalled 12.622. The share of hybrid vehicles in Germany in total number of passenger vehicles is now about 0.80%.

ELECTRIC VEHICLES

In its efforts to reduce CO₂ emissions, the current policy in many countries is very focused on electric drive motor vehicles. After the nuclear disasters in the USA (Three Mile Island), Ukraine (Chernobyl) and Japan (Fukushima), electro-mobility provides opportunities to reduce CO₂ emissions only if the electric energy is derived from the so-called renewable energy sources (water, wind, solar

energy). Since more than half of electric energy today is generated using fossil fuels (coal, oil, natural gas), the switch to electric vehicle drive does not reduce CO₂ emissions, but, on the contrary, induces its global increase.

Electric automobiles are not the discovery of today's techniques. The first electric cars were already built between 1835 and 1839 [9]. At the beginning of the 20th century, more vehicles were powered by electric motors than with IC engines. Advantages and disadvantages of electric vehicles at that time were similar to those that now follow the development of these automobiles.

Forecasts of some countries regarding the introduction of electric vehicles in the traffic sounded very seriously a few years ago. Federal Republic of Germany had a goal that 1 million vehicles in the traffic should be with pure electric drive until 2020. In 2030, that number should be increased to six million electric vehicles. China has planned that, by 2015, half a million electric vehicles should be found in traffic, and by 2020, this number should be increased by ten times - to five million vehicles [10].

The main drawbacks of electric vehicles are found, same as 150 years ago, with the battery or accumulator of electric energy or with its capacity, weight and production cost.

The capacity of the today's best batteries, Lithium-ion batteries, amounts to 0.5 kWh/l, which is 20 times less than that of gasoline and diesel fuel (9-10 kWh / l). Low capacity means great battery weight for any longer distances, which vehicle shall travel. Today, they amount to a maximum of 120 to 150 km at a flat, dry road, on a sunny, not too hot day. Turning on the lights, wipers, heating or air conditioning of the vehicle, reduces the potential radius of the vehicle by half.

Second major handicap of electric vehicles is the high production cost of battery that has been moving between 600 and 800 €/kWh for years, which is 20 to 25 times greater than for IC engines. The goal of battery price reduction is set between 200 and 300 €/kWh, which is expected to happen in about 10 years.

Electric vehicles producers are trying to reduce production costs for both electric and hybrid vehicles with using electric modules, which can be

integrated into existing vehicle platforms. Thus, the modular building system is one of more important paths of development for electric automobiles.

Listed shortcomings of electric drive, along with a lack of necessary infrastructure and standards for supply stations, cables, sockets and still great amount of time of several hours for charging the battery, have led to slow correction of ambitious plans on the share of electric vehicles in traffic.

In early 2012, there were only 4541 electric vehicles in traffic in Federal Republic of Germany or 0.01% of the total number of vehicles in traffic. In China, until this year, 7.000 electric vehicles were sold, representing 0.02% of the vehicles in traffic.

Most experts agree that, in the next 15 to 20 years, electric vehicles will not make a greater breakthrough in the market, but they will be used only for small, local fleets. According to Professor Lenz (Technical University of Vienna), electric vehicle will not at all contribute to improving the state of human environment, while, for vehicle buyers, it means a considerable increase of the price of vehicle that is significantly inferior in terms of all properties compared to IC engine drive [7].

Fuel cells

At the beginning of the 1990s, especially under the influence of development in Daimler Company, the electric vehicle drive with so-called "fuel cell" as a source of electrical energy, which was supposed to be the solution to drive the vehicle in the near future, had been euphorically presented. In the Fuel Cell electrical energy, that serves for movement of vehicle, is produced by joining the fuel (hydrogen H₂) and oxygen from the air (O₂). The other product of this chemical reaction is water (H₂O), which has no harmful effect on the human environment.

Company	Honda	Daimler	GM	Ford	Chrysler	Renault	Toyota	Nissan
Start of production	2003	2004	2004	2004	2007	2010	2015	2018
Prediction from year	(2000)	(2000)	(1998)	(2001)	(1997)	(1999)	(2004)	(2010)

Figure 8: Predictions on introduction of fuel cells in serial production

Almost all vehicle producers have invested heavily in research and development of fuel cells. Predictions about the introduction of fuel cells in mass production were very optimistic (Figure 8).

Most producers claimed that they will start the serial production in 2003 or 2004 [8, 9, 10]. To date, however, the basic weaknesses of the system have not been solved. High production cost (100 to 150 times higher than that of IC engines of the same power), lack of fuel (hydrogen has proved to be the only possible solution) and a complete lack of the necessary infrastructure for the production, distribution and storage of hydrogen have meant that the chances for application of fuel cells in road traffic are considered much smaller than the chances for battery-powered electric vehicles.

VIEW AT THE FUTURE

Accepting the advice from Andre Marlowe that "If you want to read the future, then you should scroll through the past", the past development shows that, so far, no alternative power unit has managed to threaten the primacy of IC engines. Today's parameters also show that the IC engine remains unchallenged power unit for motor vehicles.

Experts around the world mutually agree that the piston IC engine will maintain its dominant status for several decades as the main power unit for vehicles.

FUELS

They also agreed that fuels based on mineral oil and other fossil sources will not be able to meet the growing global demands for energy alone, so the answer to the question which sources of energy will be available will also carry the answer to the question of which power units will drive the future vehicles. Apparently, in the future, several fuels with similar characteristics, originating from the different sources will simultaneously exist at the market.

Conventional fuels derived from crude oil globally remain, according to today's forecasts, as the main source of energy in the next 30 years (Figure 9) - the prognosis that has been repeated for over 50 years.

Maximum exploitation of oil wells is expected in the next 15 to 20 years, after which there should be the reduction of oil supply, although the demands for energy continue to grow steadily. This fact

means that the time of cheap oil is over. With the increase in prices of oil or fuel, many alternative fuels which could not, because of their high cost, be promoted at the market until now, become economically interesting.




Figure 9: Trends in exploitation of mineral oil and natural gas resources

Relying on the European Directive on fuel quality (2003/30/EG) and direction on the use of renewable energy sources (2009/28/EG), the European Commission, in its ambitious plan to support the use of renewable energy sources in traffic, follows a specific goal that, by year 2020, at least 10% of conventional fuels in the European Union is replaced by fuels from regenerative sources [14, 15].

In the first place, there are fuels from bio-mass as fuels from renewable sources. The goal of the efforts to introduce these fuels is to enable the traffic neutral in terms of CO₂ emissions. Since the gaining of the first generation of biofuels is potentially in competition with food production and is therefore subject to harsh criticism, experts are working intensively on the next generation of biofuels, where fruit of the plant will not be used to produce fuels, but only as plant waste material. Obtaining the biofuels from algae seems especially attractive looks and it has been intensively investigated.

Beside fuels from biomass, synthetic fuels, which are likely to have greater importance in the future than it is considered now, gain more and more importance. These include:

- ETBE - Ethyl-tertiary-butyl-ester,

- Synthetic fuel obtained from natural gas (GTL, Gas to Liquid) and
- Synthetic fuel obtained from coal (CTL, Coal to Liquid).

Efforts to obtain synthetic or gaseous fuels from CO₂ emission, emitted by power plants and large industrial plants, by using excess electricity from regenerative sources or to conduct the "recycling" of CO₂, seem to be attractive.

CONCLUSIONS - MOTOR VEHICLE DRIVES IN THE NEXT 15 TO 20 YEARS

Since the liquid fuels from fossil and biogenic sources will be the main energy sources for road transport in the coming decades, the IC engine will keep its dominant position as a power unit for motor vehicles during that time. Of course, it will continue to be optimized in all phases of the operating cycles and in every detail of its construction.

The potential for further reduction of fuel consumption and CO₂ emissions is still large (Figure 10).




Figure 10: Measures for further reduction of CO₂ emission and fuel consumption

The start of power unit electrification, a hybrid drive, will probably remain a definitive solution for the foreseeable future.

Shorter and shorter intervals available for product development and introduction of innovations in engine construction, along with the growing demands regarding the conservation of natural reserves of the planet, have led to the fact that

collaboration between a producer and several partners from automobile industry has become an important factor in achieving success. Thereby, the cooperation with the so-called subcontractor industry or the suppliers has the most important role. Over 70% of the value of an automobile is created today in the suppliers. This picture will not be changed in the future.

Today, about 70 million of road vehicles are made annually in the world. In the meantime, China has become the largest producer, with annual production of over 16 million vehicles. In the next 5 years, the number of vehicles is projected to increase for more than 30%.

More than 99% of the produced vehicles will be driven by further developed IC engines. This provides the engineers in the automotive industry with safe, interesting and intensive work in the coming time.

At the end, let's repeat the conclusions, which have been repeated for decades:

1. Four-stroke piston engine stays as main power unit for motor vehicles in the next 10 to 15 years.
2. World oil reserves are secured for the next 30 to 40 years.

REFERENCES

- [1.] Gruden, D.: "On future of power units for motor vehicles" (in Serbian), MVM2010, Kragujevac, 2010
- [2.] "Zusammenwirken der Antriebskomponenten", MTZ, 73(2012) 7/8
- [3.] "Motoren mit kleinem Hubraum", MTZ, 73 (2012) 5
- [4.] Gruden, D.: "Patentschrift 25 36 775", Deutsches Patentamt, 18.8.1975; US Patent and Trademark office, 1978
- [5.] Gruden, D.: "Combustion and Exhaust Emission of an Engine Using the Porsche-Stratified-Charge-Chamber-System", SAE Paper 750888
- [6.] Schommers, J.: "Reibleistungsoptimierung – Basis für die Zukunftsfähigkeit der Verbrennungsmotoren", Daimler, Stuttgart, 2012
- [7.] 33. Internationales Wiener Motorensymposium, Wien, 2012
- [8.] Andert, J. et al.: "Range Extender von KSPG, ein neuer Wegbreiter der Elektro-mobilität" MTZ 73 (2012) 5
- [9.] Hohl, G.: "150 Jahre Elektromobilität", ÖVK, Wien, 2012

[10.] "Chinas E-Mobilitätsstrategie geht nicht auf", VDI-Nachrichten, 20.04.2012

[11.] "Automotive Engineer", January 2000

[12.] Schilke, N.A.: "US Fuel Cell Technology", President SAE International 2001

[13.] Hertel, P.: "Membranen für Brennstoffzellen", ATZ 107 (2005) 6

[14.] "Alternative Kraftstoffe", MTZ 73 (2012) 6

[15.] "Alternative fuels for transport", IFP – Energie nouvelles, Lyon, 2012



ACTA Technica CORVINIENSIS
BULLETIN OF ENGINEERING

ISSN:2067-3809

copyright ©

University "POLITEHNICA" Timisoara,

Faculty of Engineering Hunedoara,

5, Revolutiei,

331128, Hunedoara, ROMANIA

<http://acta.fih.upt.ro>